






**SPECIFICATION DATA SHEET | MODEL : 10TCG**



The **TRANSCUBE™ 10TCG** is a compact, transportable, double-walled fuel tank. Quickly and easily supply fuel where you need it, when you need it.

-  **Transportable.** Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the tank full of fuel.
-  **Stackable.** Easily stackable (2)-high full of fuel and (3)-high empty to reduce storage space requirements.
-  **Accessible.** Access manway for maintenance and inspection of inner tank. Removable inner tank for servicing and cleaning.
-  **Efficient.** Lockable equipment cabinet locks and secures equipment and fuel ports to run up to 3 pieces of diesel-powered equipment.
-  **Environmentally Safe.** Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

SPECIFICATIONS*	
STANDARD FITTINGS: High accuracy contents gauge; 3" Fill Point; 2" fusible link fill port; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return port set; pressure/vacuum vent; breather vent. OPTIONAL FITTINGS: Complete transfer pump kits; water & particulate filter kits; fuel up to (2) feed & return blocks; fuel hose & quick couplers.	
<b>Capacity (Brim-Fill) Litres:</b> 978	<b>Dimension Height (mm/in):</b> 1318 mm/51.87"
<b>Capacity (Brim-Fill) Imperial Gallons:</b> 215	<b>Weight Empty (lbs/kg):</b> 1122 lbs (509kg)
<b>Capacity (Brim-Fill) US Gallons:</b> 258	<b>Weight Full (lbs/kg):</b> 3279 lbs (1487kg)
<b>Dimension Length (mm/in):</b> 1153 mm/45.38"	<b>Approvals:</b> UL142, ULC S-601-07, SUN IBC Type 31A,
<b>Dimension Width (mm/in):</b> 1152 mm/45.34"	UN DOT, NFPA, Transport Canada, Vlare, Kiwa

\*Model specifications may slightly differ based on stock availability in your area. Please contact your local representative to confirm tank specifications.